


Warmgewalst gelijkzijdig T-staal

Statische waarden



| Benaming | Afmetingen | | | | | | Handels- gewicht | Sectie A |
|----------|------------|-----|-----|----|----------------|----------------|---------------------|-----------------|
| | h | b | s/t | r | r ₁ | r ₂ | | |
| mm | mm | | | | | | kg/m | cm ² |
| T20 | 20 | 20 | 3 | 3 | 1,5 | 1 | 0,97 | 1,12 |
| T25 | 25 | 25 | 4 | 4 | 2,0 | 1 | 1,42 | 1,64 |
| T30 | 30 | 30 | 4 | 4 | 2,0 | 1 | 1,85 | 2,26 |
| T35 | 35 | 35 | 5 | 5 | 2,5 | 1 | 2,44 | 2,97 |
| T40 | 40 | 40 | 5 | 5 | 2,5 | 1 | 3,03 | 3,77 |
| T45 | 45 | 45 | 6 | 6 | 3,0 | 1,5 | 3,74 | 4,67 |
| T50 | 50 | 50 | 6 | 6 | 3,0 | 1,5 | 4,53 | 5,66 |
| T60 | 60 | 60 | 7 | 7 | 3,5 | 2 | 6,35 | 7,94 |
| T70 | 70 | 70 | 8 | 8 | 4,0 | 2 | 8,48 | 10,60 |
| T80 | 80 | 80 | 9 | 9 | 4,5 | 2 | 10,9 | 13,60 |
| T100 | 100 | 100 | 11 | 11 | 5,5 | 3 | 16,72 | 20,90 |
| T120 | 120 | 120 | 13 | 13 | 6,5 | 3 | 23,7 | 29,60 |
| T140 | 140 | 140 | 15 | 15 | 7,5 | 4 | 31,92 | 39,90 |



| Oppervlakte | Statische waarden | | | | | |
|-------------------|-------------------|-----------------|----------------|-----------------|-----------------|----------------|
| | Sterke as y-y | | | Zwakke as z-z | | |
| A _L | I _y | W _y | i _y | I _z | W _z | i _z |
| m ² /m | cm ⁴ | cm ³ | cm | cm ⁴ | cm ³ | cm |
| 0,075 | 0,38 | 0,27 | 0,58 | 0,20 | 0,20 | 0,42 |
| 0,094 | 0,87 | 0,49 | 0,73 | 0,43 | 0,34 | 0,51 |
| 0,114 | 1,72 | 0,80 | 0,87 | 0,87 | 0,58 | 0,62 |
| 0,133 | 3,10 | 1,23 | 1,04 | 1,57 | 0,90 | 0,73 |
| 0,153 | 5,28 | 1,84 | 1,18 | 2,58 | 1,29 | 0,83 |
| 0,171 | 8,13 | 2,51 | 1,32 | 4,01 | 1,78 | 0,93 |
| 0,191 | 12,1 | 3,36 | 1,46 | 6,06 | 2,42 | 1,03 |
| 0,229 | 23,8 | 5,48 | 1,73 | 12,2 | 4,07 | 1,24 |
| 0,268 | 44,5 | 8,79 | 2,05 | 22,1 | 6,32 | 1,44 |
| 0,307 | 73,7 | 12,8 | 2,33 | 37,0 | 9,25 | 1,65 |
| 0,383 | 179 | 24,6 | 2,92 | 88,3 | 17,7 | 2,05 |
| 0,459 | 366 | 42,0 | 3,51 | 178 | 29,7 | 2,45 |
| 0,537 | - | - | - | - | - | - |